


1 Sample workflows

MCTS on verified tasks



Optimizers keep only W^* , discarding $>95\%$ of evaluated designs.

We keep every node:
 $N=20$ rounds $\times$ $K=5$ runs, failures included.

2 Build a corpus

28,568 triplets (W, T, m) , e.g.:

W : graph.py

```
class Workflow:
    async def __call__(self, problem):
        seq = operator.Sequential(
            llm=self.llm, num_rounds=2,
            prompts=[SUDOKU_SOLVE_PROMPT,
                    SUDOKU_REVIEW_PROMPT])
        solution = await seq(problem)
        return solution["response"]
```

prompt.py

```
SUDOKU_SOLVE_PROMPT = """
Solve the problem carefully. ...
Problem: {problem}"""
SUDOKU_REVIEW_PROMPT = """
Review the previous answer ...
Original problem: {problem}
Previous answer: {previous_output}"""
```

T : Sudoku, Easy

5	3		7			
6			1	9	5	
	9	8				6
8			6			3
4			8	3		1
7				2		6
	6				2	8
		4	1	9		5
			8		7	9

Grid · 20 instances

m : verified results


score	1.000
cost	\$0.1235
round	1
worker	gpt-5.4-mini
aggreg.	gpt-5.4-nano
optim.	gpt-5.4
split	train

split by search: train 69% val test

Sampling phase

3 Mine features

sandboxed AutoResearch



Analysis phase

4 Verify principles

on held-out searches:

$$\Delta = \bar{m}_{\text{has}} - \bar{m}_{\text{lacks}}$$

STAR-first entry (topology)



SHARED MEMORY (state)



Richer prompts (prompt)



-0.05 0 +.1